

FEATURES | 產品特點

Superior joint for comfortable contact.

優良的鬆緊帶搭接品質



Precise logo detecting and positioning.

精準的LOGO辨視與定位



Error detection to prevent poor feeding, ensuring sewing quality.

錯誤檢知，自動警告來料問題，確保車縫品質



Regular cutter
冷切效果



Ultra sonic cutter (Optional)
超聲波切刀 (選配)



SPECIFICATION | 產品規格

型號 Model	ASP-EBJ200
搭配縫紉機機頭 Machine Head	JUKI LK-1920 / JUKI AMS210ENSS (OPT)
車縫速度 Sewing Speed	2800 SPM (最高 Max)
使用針型 Needle Type	DPx5 #14
鬆緊帶寬度 Band Width	20mm ~ 60mm / ~ 90mm (OPT)
兩折長度 Folding Length	150~990mm (鬆緊帶圓周長度300~1980mm) 重疊尺寸 (對合) 0~13mm 150~990mm (waistband circumferences 300~1980mm) Lapping size (folded) 0~13mm
縫紉尺寸 Sewing Length	重疊尺寸 0~13mm Overlapping range 0~13mm 兩折長度 150~990mm Two folding length 150~990mm
氣體消耗量 Air Consumption	30 L/min
氣壓 Air Pressure	0.5 Mpa
電源電壓 Power Supply	Single Phase 1 Φ AC200~240V 50/60Hz
消費電力 Power Consumption	800 W (Max)
機器尺寸 Machine Dimensions	(W)1550X(D)1150X(H)1530mm (With table and thread stand 含桌板、線架)
生產效率 Production Capacity	視縫製針數而定・針數：33針・產速：5秒/件 Stitches. Total stitch: 33、Output: 5 sec/piece



高林股份有限公司
KAULIN MFG. CO., LTD.

由於對產品的改良及更新，本產品型錄之產品規格及外觀的修改恕不事先通知！

The specification and appearances of the equipment described in this catalogue are subject to change without previous notice.



ASP-EBJ200

銀箭牌

Automatic Elastic Ring Making Machine

高速自動鬆緊帶搭接機



SIRUBA
AUTOMATIC SYSTEM

